



Surface Mount Super Fast Recovery Rectifier



Features

- Super fast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Part no. with suffix "Q" means AEC-Q101 qualified

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, automotive and telecommunication.

Mechanical Data

- **Package:** DO-214AB (SMC)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes the cathode end

■ Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	ES3AQ	ES3BQ	ES3CQ	ES3DQ	ES3FQ	ES3GQ	ES3HQ	ES3JQ
Device marking code			ES3A	ES3B	ES3C	ES3D	ES3F	ES3G	ES3H	ES3J
Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	150	200	300	400	500	600
Average Rectified Output Current @60Hz sine wave, Resistance load, T_L (Fig.1)	I_O	A	3.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Ta=25°C	I_{FSM}	A	100							
Storage Temperature	T_{stg}	°C	-55 ~ +150							
Junction Temperature	T_J	°C	-55 ~ +150							

■ Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	ES3AQ	ES3BQ	ES3CQ	ES3DQ	ES3FQ	ES3GQ	ES3HQ	ES3JQ
Maximum instantaneous forward voltage drop per diode	V_F	V	$I_{FM}=3.0A$	0.95				1.3		1.7	
Maximum reverse recovery time	T_{RR}	ns	$I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$	35							
Maximum DC reverse current at rated DC blocking voltage per diode @ $V_{RM}=V_{RRM}$	I_R	μA	Ta=25°C	5							
			Ta=125°C	100							
Typical junction capacitance	C_J	pF	$V_R=4V, f=1\text{ MHz}$	60							



ES3AQ THRU ES3JQ

■ Thermal Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	ES3AQ	ES3BQ	ES3CQ	ES3DQ	ES3FQ	ES3GQ	ES3HQ	ES3JQ
Thermal Resistance	R _{θJA}	°C/W	75 ¹⁾							
	R _{θJL}		15 ¹⁾							

Note (1)

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ES3AQ-ES3JQ	F1	Approximate 0.248	3000	/	42000	13" reel

■ Characteristics (Typical)

Fig.1: I_O-T_L Curve




Fig.2: Surge Forward Current Capability




Fig.3: Forward Voltage




Fig.4: Typical Reverse Characteristics






Fig.5: Diagram of circuit and Testing wave form of reverse recovery time




■ Outline Dimensions



DO-214AB (SMC)		
Dim	Min	Max
A	6.60	7.11
B	2.85	3.27
C	5.59	6.22
D	7.75	8.13
E	1.99	2.61
F	0.15	0.31
G	0.76	1.52
H	0.05	0.20

■ Suggested pad layout



DO-214AB (SMC)	
Dim	Min
P1	9.9
P2	3.84
Q1	3.03
Q2	3.82



ES3AQ THRU ES3JQ

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, lifesaving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.