


## Small Signal Schottky Diode



**SOD323**

### Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- Low Forward Voltage Schottky Rectifier
- $V_{RRM}$  70V
- $I_{FAV}$  70mA
- Part no. with suffix "Q" means AEC-Q101 qualified

### Applications

- For Transient and ESD Protection
- Automotive

### Mechanical Data

- **Case:** SOD-323
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

### ■ Maximum Ratings ( $T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	VALUE
Repetitive Peak Reverse Voltage	$V_{RRM}$	V		70
Average Forward Current	$I_{FAV}$	mA		70
Peak Forward Surge Current	$I_{FSM}$	A	$t=8.3\text{ms}$	3
Power Dissipation	$P_{tot}$	mW		250
Thermal Resistance Junction to Ambient	$R_{thJA}$	K/W		500
Junction Temperature	$T_j$	$^\circ\text{C}$		-55 to +150
Storage Temperature Range	$T_{stg}$	$^\circ\text{C}$		-55 to +150

### ■ Electrical Characteristics ( $T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	MIN	MAX
Forward Voltage	$V_F$	V	$I_F=1\text{mA}$		0.41
			$I_F=15\text{mA}$		1
Reverse Current	$I_R$	$\mu\text{A}$	$V_R=50\text{V}$		0.2
Breakdown Voltage	$V_{BR}$	V	$I_R=10\mu\text{A}$	70	
Junction Capacitance	$C_J$	pF	$V_R=0\text{V}$ , $f=1\text{MHZ}$		4
Reverse Recovery Time	$t_{rr}$	ns	$I_F=I_R=10\text{mA}$ , $I_{rr}=1\text{mA}$ , $R_L=100\Omega$		5



# BAS70WSQ

## Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BAS70WSQ	F2	Approximate 0.0048	3000	30000	120000	7" reel

## Characteristics (Typical)

Fig.1:  $P_D-T_A$




Fig.2: Capacitance Characteristics




Fig.3: Forward Characteristics





Fig.4: Reverse Characteristics







# BAS70WSQ

## ■ Outline Dimensions

SOD-323



UNIT : mm

SUGGESTED SOLDER PAD LAYOUT

DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	---	0.0393	---	1.0000
A1	0.0000	0.0039	0.0000	0.1000
A2	0.0314	0.0354	0.8000	0.9000
b	0.0098	0.0157	0.2500	0.4000
c	0.0031	0.0059	0.0800	0.1500
D	0.0472	0.0551	1.2000	1.4000
E	0.0629	0.0709	1.6000	1.8000
E1	0.0984	0.1063	2.5000	2.7000
L	0.0187TYP		0.475TYP	
L1	0.0098	0.0157	0.250	0.400
θ	0°	8°	0°	8°

## ■ Marking Information



**Note:**

1. All marking is at middle of the product body
2. All marking is in laser marking
3. Body color: Black



## BAS70WSQ

---

### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.